

Rail drilling machine

RAIL.40S

Available in 6 different rail adapter versions:
S49, S54, TRC68, UIC50, UIC54 and UIC60.

Technical data

	Metric	Imperial
Annular cutting	Ø 12 - 36 mm	Ø 7/16" - 1 7/16"
Length	230 mm	9 1/16"
Width	180 mm	7 1/16"
Height	495 - 610 mm	19 1/2" - 24"
Stroke	155 mm	6 1/8"
Weight*	12 kg	26.5 lbs
Motor power	1,150 W	10.5 A
Total power	1,200 W	10.9 A
Speed (no load)	600 rpm	
Speed (load 1,150 W, 10.5 A)	380 rpm	
Spindle (Weldon)	19.05 mm	3/4"
Voltage	110 - 120 V / 60 Hz 220 - 240 V / 50 - 60 Hz	

* Without power cord and handles



Features:



Oil lubricated
gearbox

Benefits:

- Suitable for processing rails
- High-efficiency motor with less heat generation
- High-accuracy capstan hub
- Direct spindle drive
- Integrated slide and one-speed oil lubricated gearbox for:
 - High accuracy
 - Enlarged lifecycle
 - Minimal vibration
- High-precision height adjustment for:
 - Low maintenance
 - Minimal wear correction